

## Complete S.S weather proof Pressure Gauges



- |     |                                 |   |   |
|-----|---------------------------------|---|---|
| 1.  | <b>Dial Size</b>                | : | 100mm   |
| 2.  | <b>Accuracy</b>                 | : | ± 1 % of Fsd  |
| 3.  | <b>Bourdon</b>                  | : | S. S. – 316   |
| 4.  | <b>Movement</b>                 | : | S.S 304   |
| 5.  | <b>Socket</b>                   | : | S.S 304   |
| 6.  | <b>Case &amp; Bezel</b>         | : | S.S 304, Baynot Bezel type                            |
| 7.  | <b>Dial</b>                     | : | White Al. With Black Marking                          |
| 8.  | <b>Mounting</b>                 | : | Direct bottom connection                              |
| 9.  | <b>Connection</b>               | : | ½" NPT or BSP(M) as required                          |
| 10. | <b>Over pressure Protection</b> | : | 130 % of span   |
| 11. | <b>Window</b>                   | : | Toughened Glass                                       |
| 12. | <b>Standard Fitment</b>         | : | Micro Zero adjustment pointer<br>Blow off Disc on Top |
| 13. | <b>Temp. Limit</b>              | : | 270° C  |
| 14. | <b>Joints</b>                   | : | Argon arc welded                                      |
| 15. | <b>Range</b>                    | : | 0-20 bar  |